

Images are for refernce only. See ordering information for SKU details.

Features

- 5G sub6 Radio Modem Compatible with Lanner Vehicle PC
- 2x nano SIM Card Readers, 4x Antenna Jack, with antenna / cable kit
- SATA connector with USB 3.0 signal and Hot Swappable Capability
- 5G Failover for Constant Operations
- Designed for Network Failover and Vehicle Applications
- Swappable Caddy
- Supports NSA and SA modes

■ Preliminary Specifications

5G Modem Card

PGN-750A

- 5G NR Sub-6 Bands: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n38,
- n40, n41, n48, n66, n71, n77, n78, n79
- LTE Bands: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B30, B34, B38, B39, B40, B41, B42, B43, B48, B66,
- PGN-750B
- 5G NR Sub-6 Bands: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n38,
- n40, n41, n48, n66, n71, n77, n78, n79
- LTF Bands: B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B66, B71, B34, B38, B39, B40,
- B41 B42 B43 B46 B48 B1, B2, B3, B4, B5, B6, B8, B19
- PGN-750C
- 5G NR Sub-6 Bands: n1, n2, n3, n5, n7, n8, n12, n20, n28, n66,
- n71.n38. n41. n77. n78. n79
- LTE Bands: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B66, B71, B34, B38, B39, B41, B42,
- B48, B46

Interface

SATA connector with USB 3.0 signal

System Compatibility

Lanner Vehicle	PC V3S,	V6S,	ISD-V330
----------------	---------	------	----------

Temperature

- Operating -40~70°C
- Storage -40~85°C

Humidity

5%~90% RH. Non-condensing

Mechanical

Dimension

76 x 115.97 x 145 mm

Weight 0.4 Kg

Product I/O View





- 5G Antenna
- SIM slots
- Antenna cable
- SATA connector with USB 3.0 signal

Ordering Information

PGN-750A Swappable 5G Telit FN980 module with antenna/cable kit.

PGN-750B Swappable 5G Quectel RM500Q-AE module with antenna/cable kit.

PGN-750C Swappable 5G Thales MV31-W module with antenna/cable kit. v4-2023.09.28

