

N2S-IVMT201

Lanner N2S NIC Module With Intel® Ethernet 700 Series XXV710-DA2T & Hardware-enhanced IEEE 1588 PTP



■ Features

- Intel Ethernet 700 Series XXV710-DA2T
- Hardware-enhanced IEEE 1588 Precision Time Protocol
- Lanner N2S Standard
- 2x 25GbE QSFP
- 2x Gen4 PCIe*8 Golden Finger With 1x PCIe*16 Signal

■ Specifications

Chipset	Intel Ethernet 700 Series XXV710-DA2T
Interface	2x Gen4 PCIe*8 Golden Finger w/ 1x PCIe*16 Signal
Connector	2x 25GbE QSFP
Compatibility	Lanner Network Appliance
Temperature	Operating: 0°C~40°C Storage: -40°C~70°C
Humidity	Operating: 5°C~90°C Storage: 5°C~95°C
Mechanical	Dimension (W x D x H): 155 x 210 x 39 mm Weight: TBD
Certification	RoHS, CE/FCC Class A

■ Product I/O View



A 2x 25GbE QSFP

N2S-IVMT201

NIC Module

■ Ordering Information

N2S-IVMT201 Lanner N2S Standard NIC Module with 2x 25GbE QSFP

V.1-2022.01.24

Lanner

© Lanner Electronics Inc. All rights reserved.
All product specifications are subject to change without notice.
contact@lannerinc.com | www.lannerinc.com