HLM-EIIO

PRELIMINARY



■ Features

- Fabric interface with 6x 100GbE QSFP28, 8x 10/25GbE SFP28
- Intel Tofino Series (BFN-T10-032D-B0) the maximum bandwidth up to 3.2 Tb/s.
- Optional IEEE 1588 support
- Compatible with HTCA-E400 Series

■ Preliminary Specifications

Model	
	HLM-E110
Controller	
	Intel Tofino Series (BFN-T10-032D-B0)
Fabric Interface	
	6x 100GbE QSFP28, 8x 10/25GbE SFP28
Front Panel Interface	
	6x 100GbE QSFP28, 8x 10/25GbE SFP28
	2 RJ45 for management and console, 1x
	USB 2.0
System Compatibility	
	HTCA-E400 Series
Temperature	
Operating	0 ~ 40°C
Storage	-40~70°C
Humidity	
	5%~90%. non-condensing
Mechanical	
Dimension (W x H x D)	216.5 x 42.2 x 444 mm
Weight	TBD
Certification	
CE	Class A
FCC	Class A

■ Ordering Information

HLM-E110A 6x 100GbE QSFP28, 8x 10/25GbE SFP28 Switch Sled for HTCA-E400 Series

■ Product I/O View





- RJ45 for management and console
- **USB** port
- 100GbE QSFP28 cage
- 10/25 GbE SFP28 cage
- **Power Button**
- Reset Button

V1-2021,11,4

